

## VIRGO BXX 18 Series

### Features

- Flexible fluorescent striplight for long compact fluorescent lamps, with exceptional lumen-per-watt ratio, long rated life and superior color rendering
- Durable fixture construction, with ballasts and components from industry-leading sources
- Pre-wired and fully assembled for quick and easy installation
- UL Listed for Dry Location, surface mount
- Ideal for indirect lighting in curved spaces

### Lamp Information


- For 18W compact fluorescent lamp (2G11 base 4-pin twin tube)
- Up to 69 lumens per watt
- Color Rendering Index: 82
- Color temperatures include: 3000K, 3500K, 4100K
- Up to 20,000 hours average rated life
- Lamps not included. See chart for details.

### Fixture Construction



- 3.65 inches wide, 3.60 inches high
- Made of extruded aluminum using high-grade alloy
- Standard finishes include mill finish, anodized satin and high-reflectance white powder coat
- Flexible joiners between lamp modules allow fixture to curve along radius
- Lamp spacing is 12" on center
- Available in 72" fixture (6 lamps), 48" fixture (4 lamps) and 12" fixture (1 lamp)
- Joiners allow fixtures to be linked together for continuous row
- UL listed lampholders, rated for up to 600V, lock lamps into position
- Pre-attached mounting tabs simplify installation
- Fixtures ship pre-wired and pre-assembled
- 14 gauge lead wires provided (hot, neutral and ground)

### Standard Ballast

- Energy efficient, high power factor electronic ballast
- Flicker-free illumination
- Class A sound rating
- 120V or 277V
- 0°F minimum starting temperature, 158°F maximum case temperature
- UL Listed, Class P ballast with inherent overcurrent protection



### Fixture Lengths



### Recommended Lamps

Brand	Watts	Length	Base	Lumens	Lumens / Watt	Color Temp.	CRI	Rated Hrs.
GE High Lumen Biax	18W	10.5	2G11	1250	69	3000, 3500, 4100	82	20,000

Selected information based on specifications available from GE. Consult lamp manufacturer for full selection and current details. Lamps not included with fixture.

## How to Specify VIRGO BXX 18 Series

<b>VIR - BXX - 18 -</b>				
	<b>Ballast</b>	<b>Volts</b>	<b>Finish</b>	<b>Fixture Length</b>
	ELE    Electronic non-dimming	120    120 Volts 277    277 Volts	NAL    Natural aluminum (mill finish) SAT    Anodized satin WHT    High reflectance white powder coat	72    76" long (6 lamps) 48    48" long (4 lamps) 12    12" long (1 lamp)
<b>Example</b>				
<b>VIR - BXX - 18 -</b>	<b>ELE</b>	<b>277</b>	<b>NAL</b>	<b>72</b>